



## **Product information**

# **Classic Motor Oil SAE 15W50**

**Bardahl Classic Motor Oil SAE 15W50** is a semi-synthetic engine oil designed for lubrication of gasoline- and diesel engines with and without turbo. The synthetic base oil increases the resistance against aging and shearing. In addition, the additive package is formulated to protect the engine under every extreme circumstance at any surrounding temperature.

**Bardahl Classic Motor Oil SAE 15W50** consists of high quality synthetic and mineral base oils to which modern additive package is added. This formula provides optimum protection against wear, oxidation, dilution and the formation of Black Sludge.

Extensive tests have shown that this oil was found suitable to reduce pollution in the engine and can be used 365 days a year. This motor oil saves fuel and is safe for catalytic converters.

### **Application**

This oil meets the strictest requirements of both gasoline (even with LPG installations), with or without turbocharger / compressor. Suitable for engines after 1970.

### **Specifications**

API Service SL/CF

**Ref** 45451

**Content** 1 liter

**Ref** 42455

**Content** 5 liter

**Ref** 45482

**Content** 25 liter

**Ref** 45486

**Content** 60 liter

**Ref** 45492

**Content** 210 liter

OCD Nederland BV

Maxwellstraat 41 - 2216GP Dordrecht - Postbus 9024 - 3301 AA Dordrecht

Tel (078) 6512322 - Fax (078) 6174848 - email: [info@bardahl.nl](mailto:info@bardahl.nl) - website: [www.bardahl.nl](http://www.bardahl.nl) **45400**